

More fast & More Reliable Fingerprint Terminal

KJ-3300

KJ-3300 / KJ-3300(L)

Access control
& Time attendance



Superb algorithm

0,3sec for 2,000 fingerprints and 1sec for 50,000 fingerprints



Spoof Detection : Multi Spectral Imaging Sensor (Option)

Detect a fake by characterizing the subsurface data



Extension Phone Function (Option)

Built-in MIC speaker for internal communication



Various RF Cards

125KHz / 13.56 MHz : HID prox, Indala, EM, Mifare, iClass, Felica



IP65

Suitable for outdoor installation



Interoperable with other Fingerpass models
and PLA-SF software

KJ-3300

Features

- 
Superb algorithm
 Matching speed meets 0.3secs for 2,000 fingerprints and 1secs for 50,000 fingerprints
- 
Spoof Detection : Multi Spectral Image Sensor (Option)
 Can quickly detect a fake by characterizing the subsurface data against the known characteristics of the human skin
- 
Extension Phone Function (Option)
 Built-in MIC speaker for internal communication
- 
One of the world's fastest fingerprint readers
 2,000 fingerprints read & recognition in 0.3 seconds
 Can save up to 50,000 fingerprints and 500,000 events.
- 
Auto & 360 Direction Fingerprint Recognition
 Can read fingerprints placed in any direction
- 
2.8 inch Color TFT LCD screen display
 Displays detailed information such as date, time, user guide, and user list, etc.
- 
Language: Multiple language
 Default is Korean / English and can support multiple languages
- 
GUI / Touch Keypad
 User friendly GUI and Touch keypad provide an easy way to access the system
- 
Various RF Cards
 125KHz / 13.56MHz: HID prox, Indala, EM, Mifare, iClass, Felica
- 
IP65
 Suitable for outdoor installation

KJ-3300 / KJ-3300(L)



Specification

CPU	32bit CPU
Display	2.8" TFT Color LCD
Sensor	500 dpi Optical sensor Multi Spectra Image sensor (Option)
RF reader	125KHz / 13.56MHz (HID prox, Indala, Mifare, EM, Felica)
Communication type	TCP/IP, RS-485
External Interface	Wiegand, USB Memory Card
Fingerprint Capacity	2K, 5K, 10K, 30K, 50K
FAR / FRR	0.00001 / 0.01 (%)
Event log	Maximum 500,000 events
Operation Mode	Password/Fingerprint/card mixture
Inputs & Outputs	4In / 2Out
Power	12V DC 500mA
Produce size	115(H) x 165(W) x 49(D)mm
Certification	CE, FCC certified
Other	Firmware upgrade available Error search function available

System Layout

- Safe, secure, and economical access control system
- Any new installations can be integrated into existing access control systems
- Securing facilities, reducing costs via time management

